CORRECTED AMENDMENTS TO THE CLAIMS

- 1. (Canceled)
- 2. (Currently Amended) A control-program-development supporting apparatus that develops a control program described with a sequential-control language, such as a ladder diagram or instruction list, said control-program-development supporting apparatus comprising a compiler which compiles the control program into codes directly executable by a universal microprocessor that includes an acceleration unit, such as pipeline logic and a eache.
- 3. (Previously Presented) The control-program-development supporting apparatus according to claim 2 further comprising an optimization filtering unit which reconstructs the control program into an optimum code system by excluding not-cited variables and redundant codes and rearranging codes for locally arranging instructions for a common input or output device, wherein a control program optimized by said optimization filtering unit is newly used as the control program.
- 4. (Previously Presented) The control-program-development supporting apparatus according to claim 2, further comprising a processing-time rough-estimating unit which has a relating table which relates a sample program having a known processing time with the control program corresponding to the execution codes to estimate sequential-processing execution time of a programmable controller in accordance with the relating table.
- 5. (Currently Amended) A control-program-development supporting apparatus that develops a control program described with a sequential-control language, such as a ladder diagram-or instruction-list, said control-program-development supporting apparatus comprising:
- a control-program dividing unit which divides the control program into a plurality of blocks; and
- a compiler which compiles at least some of the blocks into execution codes directly executable by a programmable controller, wherein the programmable controller includes a microprocessor having an acceleration unit.
 - 6. (Canceled)

- 7. (Previously Presented) The control-program-development supporting apparatus according to claim 5, wherein the control program is a ladder diagram or an instruction list generated from the ladder diagram, and the control-program dividing unit divides the control program into a plurality of blocks at a predetermined rung in the ladder diagram to generate a program file for every block concerned.
- 8. (Previously Presented) The control-program-development supporting apparatus according to claim 5, wherein the control program is a ladder diagram or an instruction list generated from the ladder diagram, and the control-program dividing unit divides the control program into a plurality of blocks at a predetermined rung serving as a jump destination for a jump instruction in the ladder diagram to generate a program file for every block.
- 9. (Currently Amended) The control-program-development supporting apparatus according to claim 5, wherein

the control program is a ladder diagram or an instruction list generated from the ladder diagram, and

the control-program dividing unit extracts at least some rungs including instructions to a common input or output device from the ladder diagram, constitutes one block of at least some of the rungs extracted <u>constituting one block</u>, and generates a program file for every block.

- 10. (Previously Presented) The control-program-development supporting apparatus according to claim 5 further comprising an optimization filtering unit which reconstructs the control program into an optimum code system by excluding not-cited variables and redundant codes and rearranging codes for locally arranging instructions for a common input or output device, wherein a control program optimized by said optimization filtering unit is newly used as the control program.
- 11. (Previously Presented) The control-program-development supporting apparatus according to claim 5, further comprising a processing-time rough-estimating unit which has a relating table which relates a sample program having a known processing time with the control program corresponding to the execution codes to estimate a sequential-processing execution time of a programmable controller in accordance with the relating table.
- 12. (Currently Amended) A control-program-development supporting apparatus that develops a control program described with a sequential-control language, such as a ladder

diagram or instruction list, said control-program-development supporting apparatus comprising:

a control-program dividing unit which divides the control program into a plurality of blocks;

a control-program converting unit which converts at least some of the blocks into advanced high-level-language control programs described with a universal-computer-readable advanced high-level language for every block; and

a compiler which compiles at least some of universal-computer-readable advanced high-level programming languages corresponding to every block into codes directly executable by a programmable controller.

- 13. (Currently Amended) The control-program-development supporting apparatus according to claim 12, wherein the programmable controller is provided with a universal microprocessor that includes an acceleration unit, such as pipeline logic and a cache.
- 14. (Previously Presented) The control-program-development supporting apparatus according to claim 12, wherein

the control program is a ladder diagram or an instruction list generated from the ladder diagram, and

the control-program dividing unit divides the control program into a plurality of blocks at a predetermined rung in the ladder diagram to generate a program file for every block.

- 15. (Previously Presented) The control-program-development supporting apparatus according to claim 12, wherein the control program is a ladder diagram or an instruction list generated from the ladder diagram, and the control-program dividing unit divides the control program into a plurality of blocks at a predetermined rung, serving as a jump destination for a jump instruction in the ladder diagram, to generate a program file for every block.
- 16. (Previously Presented) The control-program-development supporting apparatus according to claim 12, wherein

the control program is a ladder diagram or an instruction list generated from the ladder diagram, and

the control-program dividing unit extracts at least some of rungs including instructions to a common input or output device from the ladder diagram, constituting one block of at least some of the extracted rungs, and generates a program file for every block.

- 17. (Previously Presented) The control-program-development supporting apparatus according to claim 12 further comprising an optimization filtering unit which reconstructs the control program into an optimum code system by excluding not-cited variables and redundant codes and rearranging codes for locally arranging instructions for a common input or output device, wherein a control program optimized by said optimization filtering unit is newly used as the control program.
- 18. (Original) The control-program-development supporting apparatus according to claim 12, further comprising:
- a processing-time rough-estimating unit which has a relating table which relates a sample program having the processing time already known with the control program corresponding to the execution codes to estimate a sequential-processing execution time of a programmable controller in accordance with the relating table.
- 19. (Currently Amended) A control-program-development supporting apparatus that develops a control program described with a sequential-control language, such as a ladder diagram or instruction-list, said control-program-development supporting apparatus comprising:
- a control-program converting unit which converts the control program into an advanced a high-level-programming-language control program described with a universal-computer-readable advanced high-level programming language;
- a debugging-code generating unit which generates a debugging control program by inserting a line number into a part corresponding to each line, constituting the instruction list in source codes, constituting the <u>advanced</u>high-level-programming-language control program; and
- a debugging executing unit which displays each line of the instruction list and the execution part of the <u>advanced</u>high-level -programming-language control program by relating the former with the latter.

20-22. (Canceled)

23. (Currently Amended) A programmable controller which performs sequential processing in accordance with a control program described with a sequential-control

language, such as a ladder diagram or instruction list, said programmable controller comprising:

a storing unit which stores the control program;

an instruction counting unit which counts the appearance frequency of each instruction used for execution of the control program;

a pattern-matching-table generating unit which generates a pattern-matching table in which instructions are listed starting with the highest appearance frequency in accordance with results counted by the instruction-counting unit; and

an interpreting unit which executes the control program while pattern-matching the instructions listed in the pattern-matching-table in order and interpreting the control program into codes directly-executable by the programmable controller.

24. (Currently Amended) A control-program-development supporting apparatus that develops a control program described with a sequential-control language, such as a ladder diagram or instruction list, said control-program-development supporting apparatus comprising:

an instruction counting unit which counts the appearance frequency of each instruction used for the control program;

a pattern-matching-table generating unit which generates a pattern-matching table in which instructions are listed starting with the highest appearance frequency, in accordance with results counted by the instruction-counting unit; and

a compiler which compiles the control program into codes directly executable by the programmable controller while pattern-matching the instructions listed in the pattern matching table in order.

- 25. (Currently Amended) A programmable controller that performs sequential processing in accordance with execution codes generated by compiling a control program, said programmable controller comprising:
 - a storing unit which stores the execution codes;
- a universal microprocessor including an acceleration unit, such as a pipeline logic and a eache, and directly executing the execution codes; and

a control-program-development supporting apparatus that develops a control program described with a sequential-control language, such as a ladder diagram or instruction-list, the control-program-development supporting apparatus having a compiler which compiles the control program into codes directly executable by a universal microprocessor that includes an acceleration mounting unit, such as a pipeline logic and a cache.

- 26. (Currently Amended) A programmable controller that performs sequential processing in accordance with execution codes generated by compiling a control program, said programmable controller comprising:
 - a storing unit which stores the execution codes;
- a universal microprocessor which includes including an acceleration mounting units such as pipeline logic and a cache, and directly executing the execution codes; and
- a control-program-development supporting apparatus that develops a control program described with a sequential-control language such as a ladder diagram or instruction list, the control-program-development supporting apparatus having,
- a control-program dividing unit which divides the control program into a plurality of blocks; and
- a compiler which compiles at least some of the blocks into execution codes directly executable by a programmable controller.
- 27. (Currently Amended) A programmable controller that performs sequential processing in accordance with execution codes generated by compiling a control program, said programmable controller comprising:
 - a storing unit which stores the execution codes;
- a universal microprocessor which includes including an acceleration mounting unit; such as pipeline logic and a cache; and directly executing the execution codes; and
- a control-program-development supporting apparatus that develops a control program, described with a sequential-control language such as a ladder diagram or instruction-list, the control-program-development supporting apparatus having,
- a control-program dividing unit which divides the control-program into a plurality of blocks;
- a control-program converting unit which converts at least some of the blocks into advanced high-level-language control programs described with a universal-computer-readable advanced high-level language for every block; and
- a compiler which compiles at least some of universal-computer-readable advanced <u>high-level</u> programming languages corresponding to every block into codes directly executable by a programmable controller.
- 28. (Currently Amended) A programmable controller that performs sequential processing in accordance with execution codes generated by compiling a control program, said programmable controller comprising:
 - a storing unit which stores the execution codes;

- a universal microprocessor including an acceleration mounting unit, such as pipeline logic and a cache, and directly executing the execution codes; and
- a control-program-development supporting apparatus that develops a control program described with a sequential-control language, such as a ladder-diagram or instruction list, the control-program-development supporting apparatus having,
- a control-program converting unit which converts the control program into an advanced a high-level-programming-language control program described with a universal-computer-readable advanced high-level programming language;
- a debugging-code generating unit which generates a debugging control program by inserting a line number into a part corresponding to each line constituting the instruction list, in source codes constituting the <u>advanced</u>high-level-programming-language control program; and
- a debugging executing unit which displays each line of the instruction list and the execution part of the <u>advanced</u>high-level-programming-language control program by relating the former with the latter.
- 29. (Currently Amended) A programmable controller that performs sequential processing in accordance with execution codes generated by compiling a control program, said programmable controller comprising:
 - a storing unit which stores the execution codes;
- a universal microprocessor including an acceleration unit, such as pipeline logic and a eache, and directly executing the execution codes; and
- a control-program-development supporting apparatus that develops a control program described with a sequential-control language such as a ladder diagram or instruction list, the control-program-development supporting apparatus having,
- an instruction counting unit which counts the appearance frequency of each instruction used for the control program;
- a pattern-matching-table generating unit which generates a pattern-matching table in which instructions are listed starting with the highest appearance frequency in accordance with results counted by the instruction-counting unit; and
- a compiler which compiles the control program into codes directly executable by the programmable controller while pattern-matching the instructions listed in the pattern matching table in order.
- 30. (Currently Amended) A programmable controller which performs sequential processing in accordance with execution codes generated by compiling a control program, comprising:

- a first storing unit which stores the execution codes;
- a second storing unit which stores the data for the difference between an execution code stored in the first storing unit and a new execution code;
 - a microprocessor directly executing the execution codes;
- a patch processing unit which changes an execution code currently executed to a new execution code at a predetermined timing in accordance with the difference data and continuously executing the changed execution code; and

a control-program-development supporting apparatus that develops a control program described with a sequential-control language, such as a ladder diagram or instruction list, the control-program-development supporting apparatus having a compiler which compiles the control program into codes directly executable by a universal microprocessor that includes an acceleration unit, such as pipeline logic and a cache.

31. (Canceled).

32. (Currently Amended) A programmable controller which performs sequential processing in accordance with a control program described with a sequential-control language, such as a ladder diagram or instruction list, said programmable controller comprising:

a storing unit which stores the control program;

an instruction counting unit which counts the appearance frequency of each instruction used for the control program;

a pattern-matching-table generating unit which generates a pattern-matching table in which instructions are listed starting with the highest appearance frequency in accordance with results counted by the instruction-counting unit;

an interpreting unit which executes the control program while pattern-matching the instructions listed in the pattern-matching table in order and interpreting the control program into codes directly-executable by the programmable controller; and

a control-program-development supporting apparatus that develops a control program described with a sequential-control language such as a ladder diagram or instruction list, the control-program-development supporting apparatus having a compiler which compiles the control program into codes directly executable by a universal microprocessor that includes an acceleration unit, such as pipeline-logic and a cache.

33. (New) The control-program-development supporting apparatus according to claim 2 wherein said acceleration unit includes pipeline logic and a cache.

- 34. (New) The programmable controller according to claim 24 wherein said acceleration unit includes pipeline logic and a cache.
- 35. (New) The programmable controller according to claim 26 wherein said acceleration mounting unit includes pipeline logic and a cache.
- 36. (New) The programmable controller according to claim 27 wherein said acceleration mounting unit includes pipeline logic and a cache.
- 37. (New) The programmable controller according to claim 28 wherein said acceleration mounting unit includes pipeline logic and a cache.